BACK BAR EQUIPMENT

Model: **BB69N**

Natural Refrigerant R-290 Model

69" Back Bar Cooler

Textured baked black enamel finish exterior, stainless steel countertop, interior back and side panels with reinforced stainless steel floor.



Options and Accessories

(upcharge and lead times may apply)	
Add'l epoxy-coated shelves	Condensing unit on right
Stainless steel shelves	Wine rack
Food storage rated stainless steel interior (NSF-7)	Casters or legs
Riser base* (field installed)	

Consult factory for other model configurations, options and accessories.

* Adding a Riser Base increases overall height 2"

Project Name:	
Model Specified:	
Location:	
Item No:	Quantity:
AIA #:	SIS #:

Standard Model Features

REFRIGERATION SYSTEM

Performance-rated front breathing refrigeration system Natural, environmentally-safe, high-efficiency R-290 refrigerant¹ Automatic, hot gas condensate evaporator Extra large, balanced evaporator coil

CABINET ARCHITECTURE

High density, non-CFC polyurethane foamed-in-place insulation Front, rear and side venting louvered grills Magnetic snap-in door gaskets Cylinder-keyed security lock in each door Stainless steel reinforced threshold

MODEL FEATURES

Low profile cabinet design Electronic controller w/digital display & hi-low alarm LED interior lighting Easily accessible and serviceable slide-out condensing unit

¹ R-290 refrigerant meets all federal and state regulatory requirements.



Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

APPROVAL:

Model Specifications

DIMENSIONAL DATA 26 (736 cu l) Net Capacity (cu. ft.) Width, Overall (in.) 69 (1753 mm) Depth, Overall (in.) 29 3/16 (741 mm) (incl. handles & bumpers) 25 (635 mm) Depth, Body Only (in.) (less doors) 34 3/4 (883 mm) Height, Overall (in.) 3 Capacity: # Barrel Kegs Capacity: # Straight Wall Kegs 3 Capacity : # 1/6 Size Kegs 12 No. of Doors 2 No. of Shelves 4

REFRIGERANT DATA

Condensing Unit Size (H.P.)	1/4
Capacity (BTU/Hr)*	2250

ELECTRICAL DATA


Voltage (int'l)	115/60/1 (220/50/1)
Feed Wires (incl. ground)	3
Total Amps (int'l)	3.7 (3.4)
10 ft. Cord/Plug [attached] (int'l)	Yes (No)

SHIPPING DATA

Weight (lbs.)	415 (188 kg)
Height - Crated (in.)	46 (1168 mm)
Width - Crated (in.)	78 (1981 mm)
Depth - Crated (in.)	42 (1067 mm)

* Rating @ +25°F evaporator, 90°F ambient

Figures in parentheses reflect metric equivalents rounded to the nearest whole unit.





Toll-Free: 800-523-7138 Phone: 215-244-1400 Fax: 215-244-9579

539 Dunksferry Road Bensalem, PA 19020 www.continentalrefrigerator.com

MADE IN THE U.S.A.


Due to our continued efforts in developing innovative products, specifications subject to change without notice.




Intertek

Copyright 2019. Continental Refrigerator. A Division of National Refrigeration & Air Conditioning Products, Inc.

Model Plan Views





IMPORTANT NOTE: Models are completely front breathing and take in and exhaust air through the front grill. For proper operation, the area in front of the cabinet **must** not be obstructed in any way. A clearance of 1" on the back and 3" on the sides is recommended.