

# Coolscapes® Reach-In Refrigerator

Project \_\_\_\_\_  
Item \_\_\_\_\_  
Quantity \_\_\_\_\_  
CSI Section 11400  
Approved \_\_\_\_\_  
Date \_\_\_\_\_

## Models

- GBR1P-G
- GBR2P-G
- GBR3P-G
- GBR1P-GH
- GBR2P-GH
- GBR3P-GH



GBR1P-GH

## Standard Features

- GreenGenius™ R290 top mount refrigeration system featuring TXV expansion valve and hot gas condensate removal
- Digital exterior temperature display with high/low temp visual alarms
- Energy saving LED interior light
- Removable side louver
- Accommodates full size sheet pans
- Gray epoxy coated shelves (3 per section) with shelf bridge
- Smart door hinge that auto closes up to 90° and stays open past 90°
- Integral door handle
- 180° door opening
- Energy efficient door gasket – removable without tools
- Locking doors
- 5" locking casters shipped loose for field installation
- 10' cord and plug attached
- Stainless steel front shroud
- Stainless steel exterior sides
- Gray coated aluminum interior (Series GB)
- Stainless steel interior floor
- Field rehingable doors - full height doors only
- Stainless steel pilaster with shelf clips
- Vapor lock relief valve
- Three year parts and labor warranty and an additional two year compressor parts warranty

## Options

- GC Series feature set (includes pins, aluminum interior/exterior, no PRV)
- GBS Series feature set (stainless steel interior in lieu of standard aluminum interior)

## Specifications

Refrigeration system : All components are mounted to the top cabinet ceiling, outside the food zone and are assembled as one piece and can be removed as one piece. Environmentally friendly R290 refrigerant is used. System has the capability of maintaining between 33°F and 40°F in heavy use food service operations. Refrigerant is metered using a highly responsive thermostatic expansion valve. System is controlled using an electronic temperature control, which provides improved pull down times, reducing compressor cycling and longer compressor life with lower energy consumption. Control system uses

adaptive defrost to assure evaporator coil is free of ice and operating at optimum efficiency. Evaporator condensate is eliminated using an energy efficient hot gas system.

Units are completely insulated with high density foamed in place environmentally friendly, Kyoto Protocol Compliant, Non ODP (Ozone Depletion Potential), Non GWP (Global Warming Potential) polyurethane.



Coolscapes® Reach-In Refrigerator

# Coolscaapes® Reach-In Refrigerator

**Plan View All 1 Section Models**  
 27.40" (69.5 cm) width, 32.51" (82.5 cm) height, 23.44" (59.54 cm) interior width.

**Plan View All 2 Section Models**  
 55.22" (140.25 cm) width, 32.51" (82.5 cm) height, 51.26" (130.19 cm) interior width.

**Plan View All 3 Section Models**  
 83.03" (210.9 cm) width, 32.52" (82.6 cm) height, 79.07" (200.84 cm) interior width.

**Elevation View All 1 Section Models**  
 79.48" (201.8 cm) height.

**Elevation View All 2 Section Models**  
 79.48" (201.8 cm) height.

**Elevation View All 3 Section Models**  
 79.48" (201.8 cm) height.

**Side View All Models**  
 79.41" (201.7 cm) height, 27.23" (69.1 cm) depth, 13.00" (33 cm) top panel height, 5.06" (12.8 cm) bottom panel height, 56.61" (143.7 cm) interior height.

**Door Swing All Models**  
 25.98" (65.9 cm) door depth.

- Available with full or half stainless steel doors.
- Available with aluminum or stainless steel exterior sides.

Energy star® rated models	
Model	Energy kWh
GBR1P-G	2.08
GBR1P-GH	1.66
GBR2P-G	3.18
GBR2P-GH	2.91
GBR3P-G	4.92
GBR3P-GH	4.55

Specifications								
Description	Model	V/Hz/ph	Amps	# of Shelves	Volume	H.P.	Nema Plug	Ship Weight
1-section Refrigerator	GBR1P-G(H)	115/60/1	4.2	3	21ft3/595L	.22	5-15P	236lbs/107kg
2-section Refrigerator	GBR2P-G(H)	115/60/1	6.0	6	46ft3/1303L	.33	5-15P	322lbs/146kg
3-section Refrigerator	GBR3P-G	115/60/1	6.5	9	71ft3/2010L	.355	5-15P	485lbs/220kg

Welbilt reserves the right to make changes to the design or specifications without prior notice.