



Item #: Project: ____ Qty:_ AIA#: H9320 FILTER Single, Double, Triple *height includes manifold and cartridge E-10 PREFILTER (9795-80)E-20 PREFILTER (9795-90)**Single Configuration** 18.4" H 20 E-10 E-20 PREFILTER PREFILTER (9795-80) (9795-90) Recommended for Recommended for single configuraton twin and triple configuraton E-10 and E-20 Prefilters can be used for ice. Everpure **Double Configuration Triple Configuration** prefilters are designed to increase the life of Hoshizaki 19.11" H^{*}* 19.15" H 4HC-H water filters in areas with an unusual amount of dirt in the water. With a 10 micron (nominal) rating, the economical Everpure prefilter traps much of the dirt Keep ice makers functioning at full capacity which contributes to scale buildup in ice makers, and clogs the delicate orifices of other water-using equiment. 93.7% average reduction of chlorine from incoming water supply. eliminating tastes and odors of the ice When you install an Everpure prefilter, the Hoshizaki 4HC-H water filters can concentrate on what they do best: Filters are rated as one (1) micron nominal producing crystal clear ice remove particles one (1) micron nominal and larger in size. Decrease machine maintenance by reducing lime scale build-up **Replacement Cartridges:** E-10 Prefilters: 12 pack (9534-12) **HOSHIZAKI H9320 FILTER** 40 pack (9534-40) Available in single, double and triple configurations. Rated NSF Class 1, STD 42, for taste, 6 pack (9534-26) F-20 Prefilters: odor and chlorine reduction and for mechanical filtration (95.6% removal of particles one 20 pack (9534-20) (1) micron and larger in size.) The H9320 Filters and their respective cartridges have been tested and listed by NSF only for the functions listed above. Check for compliance with state and local laws and regulations. Do not use where the water is microbiologically unsafe, or with waters of unknown quality without adequate disinfection before or after the unit. The H9320 filter can be used with water that may contain filterable cysts. The H9320 System is tested and certified by NSF International



The H9320 System is tested and certified by NSF International against NSF/ANSI Standard 42 for the reduction of: **Std. No. 42 - Aesthetic effects** *Aesthetic Effects Bacteriostatic Effects Mechanical Filtration* Bacteriostatic Effects *Nominal Particulate Class 1 Chemical Reduction* Taste & Odor Chlorine

Printed in the U.S.A.

Warranty:

One Year replaceable elements*

* Warranty applies to material defects in materials & workmanship only

Hoshizaki reserves the right to change specifications without notice.

One Year the entire system





	Model Number	Description Flow Rate (Gal. per min.)	Undercounter KMs	KM Cubers	IM Cubers	Cubelets & Flakers	DCM/DBs
	H9320-51	Single (2 GPM)	AM-50 KM-80 KM-115 KM-160 KM-230 KM-300	KM-350, 520, 660 KML-325, 500, 700 KMD-410, 460, 530 KMS-830 DKM-500	IM-200, 500	All Models	All Models
	H9320-52	Twin 2 x (2 GPM)	N/A	KM-901, 1100, 1340 KMD-860 KMS-822, 1122, 1402	N/A	N/A	N/A
	H9320-53	Triple 3 x (2 GPM)	N/A	KM-1301, 1601, 1900, 2200, 2600 KMH-2100 KMS-2000	N/A	N/A	N/A
	H9655-11	Replacement Cartridge (1) One each					

Recommended water filter configurations based on average ice machine usage and regular filter replacement. If your operation has challenging water conditions or higher usage, then it may be necessary to use an additional filter or prefilter.