

RM-7-HC 08/10/20 Item # 13408

WxDxH 21.25" x 25" x 37.75"





# **Features**

- Curved vertical corners with silver aluminum exterior provide enhanced product display
- Energy efficient vertical LED interior lights illuminate products on display

• Large glass door are energy efficient low E multi pane

Spring assisted self-closing door with stay open

Stackable (three units high) to conserve warehouse

· Refrigerant flow is controlled with a capillary tube

• (3) epoxy coated wire shelves are standard

► Forced-air evaporator for quick temperature pull-down





**Dimensions / Capacity** 







	UIMI-1-UC
Interior Storage Capacity (CF)	5.97 ft <sup>3</sup>
Overall Width x Depth	21.25" x 25"
Depth with door open	44.88"
Height	37.75"
Adjustable Shelves	2 adjustable, 1 floor shelf
Shelf Dimensions (W x D)	17.75" x 20.75"
Floor Shelf Dimensions (W x D)	18" x 9.25"
Crated Shipping Weight	180 lbs.
Crated Width x Depth x Height	28" x 24.5" x 44"
Electrical / Refrigeration	One Section RM-7-HC
Voltage	115/60/1
Voltage HACR Breaker	115/60/1 15.0 Amps
•	
HACR Breaker	15.0 Amps
HACR Breaker Electrical Connection (NEMA)	15.0 Amps 5-15P 🕠
HACR Breaker Electrical Connection (NEMA) Voltage Range	15.0 Amps 5-15P 🙃 104-126
HACR Breaker Electrical Connection (NEMA) Voltage Range Ambient Temp. Range	15.0 Amps 5-15P (*) 104-126 60° to 86°F
HACR Breaker  Electrical Connection (NEMA)  Voltage Range  Ambient Temp. Range  Control Setpoint Range	15.0 Amps 5-15P ① 104-126 60° to 86°F 28° to 40°F
HACR Breaker  Electrical Connection (NEMA)  Voltage Range  Ambient Temp. Range  Control Setpoint Range  Amperage	15.0 Amps 5-15P 104-126 60° to 86°F 28° to 40°F 3.2

### **Options**

☐ Floor Epoxy Shelf (HS-5344) ☐ Epoxy Shelf (HS-5343)

One	Section
DI/	1_7_HC

5.97 ft <sup>3</sup>
21.25" x 25"
44.88"
37.75"
2 adjustable, 1 floor shelf
17.75" x 20.75"
18" x 9.25"
180 lbs.
28" x 24.5" x 44"
One Section RM-7-HC
115/60/1
15.0 Amps
5-15P 🕦
104-126
60° to 86°F
28° to 40°F
3.2
1.38
582 (1/8HP)

Warranty 3 Year - parts and Labor on entire machine.

5 Year - Parts on Compressor

Valid in United States, Canada, Puerto Rico and U.S. Territories. Contact factory for warranty in other countries.

- · Three years parts and labor warranty
- · Five year compressor warranty

• 2 inch leveling legs standard

• 8 ft. cord and plug

Capacity:

feature


floor space


20 oz. bottles: 102 12 oz. bottles: 217

Container Qty: 144




FRONT VIEW SIDE VIEW






# **PLAN VIEW**



# **HEADER DIMS**



#### **Graphic Requirements:**

- 360 dpi resolution. Scale 1=1
- Colors for CMYK process
- Image with 1/4" of excess by side
- Graphics must be saved in photoshop (with layers)
  - (or your sign company file type requirements)
- Include a full color print out

#### Material Requirements:

• 3M exterior grade UV resistant vinyl adhesive

Note: Texts and important parts of the image should be within the visible area. The visible area is illustrated by dotted lines when it applies.