



Mirage® Drop-In Induction Ranges

DESIGNED FOR LIGHT COMMERCIAL SAUTÉ AND WARMING STATIONS

- Cutting-edge dial control with high-speed power and temperature level adjustment – includes 1- to 180-minute timer function
- Bright LED digital readout is easy to see
- Temperature memory – powers up to the last-used temperature setting

1 ONE YEAR WARRANTY



*International models only



| ITEM # | DESCRIPTION | MAX PAN SIZE IN (CM) | DIMENSIONS (L X W X H) IN (CM) | VOLTAGE | KW | AMPS | PLUG | CASE LOT |
|-----------------|-------------|----------------------|------------------------------------|---------|-----|------|---------|----------|
| RANGES | | | | | | | | |
| 59501 | US | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 120 AC | 1.4 | 12 | 5-15P | 1 |
| 59601 | Europe | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | 1.8 | 7.8 | Schuko | 1 |
| 59602 | UK | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | 1.8 | 7.8 | UK | 1 |
| 59603 | China | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | 1.8 | 7.8 | China | 1 |
| 59605 | Australia | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | 1.8 | 2.8 | AU2-15R | 1 |
| WARMERS* | | | | | | | | |
| 5950145 | US | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 120 AC | .45 | 3.8 | 5-15P | 1 |
| 5950170 | US | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 120 AC | .7 | 5.8 | 5-15P | 1 |
| 59641 | Europe | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | .65 | 2.8 | Schuko | 1 |
| 59642 | UK | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | .65 | 2.8 | UK | 1 |
| 59643 | China | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | .65 | 2.8 | China | 1 |
| 59645 | Australia | 14 (35.6) | 14½ x 12½ x 2⅞ (36.8 x 31.8 x 7.3) | 230 AC | .65 | 2.8 | AU2-15R | 1 |

* Warming unit only – not a cooking range

International Models

Professional Series Drop-In Induction Ranges

DESIGNED FOR SAUTÉ, SAUCE POTS, AND SMALL STOCK POTS

- 100 settings for precise cooking control – set to power level or temperature setting
- Continuous-duty induction circuitry for non-stop cooking
- Firewall-protected circuitry with oversized fans and 18-gauge heavy-duty 18-8 stainless steel casing
- 1- to 180-minute timer – unit shuts off at end of cycle



USMADE
OF US & GLOBAL MATERIALS

2 TWO YEAR WARRANTY



| ITEM # | DESCRIPTION | MAX PAN SIZE IN (CM) | DIMENSIONS (L X W X H) IN (CM) | VOLTAGE | MAX KW | AMPS | PLUG | CASE LOT |
|--------|--------------------------------|----------------------|-----------------------------------|------------|--------|------|-------|----------|
| 69521* | Drop-In | 14 (35.6) | 16½ x 17¾ x 4¾ (41.9 x 43.2 x 12) | 208/240 AC | 2.9 | 12.1 | 6-20P | 1 |
| 69524* | Dual Hob Drop-In Front to Back | 12 (30.5) | 17¾ x 27¾ x 5¾ (44.1 x 70.8 x 13) | 208/240 AC | 2.9 | 24.2 | 6-30P | 1 |

* 69521 and 69524 Control Box Cutout Dimensions: 7¼" x 3⅞" (18.4 x 9.8 cm)

Ultra Series Drop-In Induction Ranges

DESIGNED FOR LARGE-VOLUME AND HEAVY-DUTY USAGE

- 100 power settings for precise cooking control
- Sensitive low-end control for cooking delicate sauces, crèmes, and chocolates
- 90% efficiency versus 40% for gas stoves
- 6' (183 cm) cord and plug – 3' (91.4 cm) remote control cord

USMADE
OF US & GLOBAL MATERIALS



2 TWO YEAR WARRANTY



| ITEM # | DESCRIPTION | MAX PAN SIZE IN (CM) | DIMENSIONS (L X W X H) IN (CM) | VOLTAGE | MAX KW | AMPS | PLUG | CASE LOT |
|--------|--------------------------------|----------------------|-------------------------------------|------------|--------|------|-------|----------|
| 69505 | Drop-In | 14 (35.6) | 16¾ x 17¾ x 4½ (42.5 x 44.8 x 11.4) | 208/240 AC | 3.5 | 14.6 | 6-20P | 1 |
| 69508 | Dual Hob Drop-In Front to Back | 12 (30.5) | 27¾ x 17¾ x 4¾ (70.8 x 44.1 x 12.1) | 208/240 AC | 3.5 | 29.2 | 6-50P | 1 |

69505/69508 Control Box Cutout Dimensions: 7¼" x 3⅞" (18.4 x 9.8 cm) – Note: 1 Control Per Hob